# Fuseholders

## For Low Voltage 3AG or SFE Fuse Applications

## RoHS Twist-Lock In-Line Type

**SPECIFICATIONS:**

**Electrical:** Intended for use at 32 volts or less with fuses rated up to 20 amperes when the proper spring is installed for fuse size.
**Molded Parts:** Black Thermoplastic (UL 94V2).
Body halves have a .14" diameter hole for insulated wire.
**Ambient Temperature:** –40°C to +75°C.
**Contact Rivet:** Brass. Tin finish. Designed to accommodate #14 AWG stranded wire.
**Assembled:** Includes fuse listed and 19" loop of #14 AWG red vinyl insulated wire.
**Unassembled:** For assembly to #14 AWG wire.
**OPTIONS:**
**150** 215 is similar to **155** 120A except no fuse is supplied. It is intended for use with 3AG fuses rated up to 20 amperes.
**UNIVERSAL IN-LINE FUSEHOLDER 155** 100**:**
Supplied with 8" loop of #14 AWG red vinyl insulated wire and two springs in different lengths to accommodate SFE sized fuses.

*** Please refer to Fuseology section for information on proper fuseholder de-rating.**




**ORDERING INFORMATION:**

| Unassembled | | Assembled | |
|---|---|---|---|
| Catalog Number | For Fuse Size | Catalog Number | Fuse Installed |
| **155** 104U | 1/4" x 5/8" | **155** 104A | SFE 4 |
| **155** 106U | 1/4" x 3/4" | **155** 106A | SFE 6 |
| **155** 17.5U | 1/4" x 7/8" | **155** 17.5A | SFE 7 1/2 |
| **155** 109U | 1/4" x 7/8" | **155** 109A | SFE 9 |
| **155** 114U | 1/4" x 1 1/16" | **155** 114A | SFE 14 |
| **155** 120U | 1/4" x 1 1/4" | **155** 120A | SFE 20 |

## RoHS Heavy-Duty Bayonet Knob In-Line Type

**SPECIFICATIONS:**

**Electrical:** Intended for use at 32 volts or less with fuses rated up to 20 amperes when the proper spring is installed for full size.
**Molded Parts:** Body and knob are Black Thermoset (UL 94V0). Both body and knob have a .20" diameter hole for insulated wire.
**Knob:** Bayonet-lock type metal insert.
**Ambient Temperature:** –40°C to +125°C.
**Contact Rivet:** Brass. Tin plated. Designed to accommodate #14 AWG stranded wire.
**Assembled:** Includes fuse listed and 19" loop of #14 AWG red vinyl insulated wire.
**Unassembled:** For assembly to #14 AWG wire.
**OPTIONS:**
**150** 079 is similar to **155** 020A except no fuse is supplied. It is intended for use with 3AG fuses rated up to 20 amperes.
**UNIVERSAL IN-LINE FUSEHOLDER 150** 145**:**
Supplied with 15" loop of #14 AWG red vinyl insulated wire and three springs in different lengths to accommodate SFE sized fuses.
Fuseholders with other wire sizes or lengths available on special order.

*** Please refer to Fuseology section for information on proper fuseholder de-rating.**




**ORDERING INFORMATION:**

| Unassembled | | Assembled | |
|---|---|---|---|
| Catalog Number | For Fuse Size | Catalog Number | Fuse Installed |
| **155** 004U | 1/4" x 5/8" | **155** 004A | SFE 4 |
| **155** 006U | 1/4" x 3/4" | **155** 006A | SFE 6 |
| **155** 07.5U | 1/4" x 7/8" | **155** 07.5A | SFE 7 1/2 |
| **155** 009U | 1/4" x 7/8" | **155** 009A | SFE 9 |
| **155** 014U | 1/4" x 1 1/16" | **155** 014A | SFE 14 |
| **155** 020U | 1/4" x 1 1/4" | **155** 020A | SFE 20 |

## RoHS 2AG or 5 x 20mm Inline Fuseholders

**SPECIFICATIONS:**

**Electrical:** This fuseholder, part number 150274, is intended for use with 2AG and 5 x 20mm fuses. Maximum current ratings are 5 amperes at 32V for the 2AG size fuses and 10 amperes at 32V for the 5 x 20mm size fuses.
**Body:** Black Thermoplastic.
**Terminals:** Brass.
**Wire:** 16 Awg size; nominal o.d. 0.104"; color red.
**Lead Pull Test:** Will withstand 10 lb. pull.
**Ambient Temperature:** –40°C to +80°C.
**ORDERING INFORMATION:**
**Catalog Number: 150** 274

*** Please refer to Fuseology section for information on proper fuseholder de-rating.**