Fuseholders

For Low Voltage 3AG or SFE Fuse Applications

RoHS Twist-Lock In-Line Type

SPECIFICATIONS:

Electrical: Intended for use at 32 volts or less with fuses rated up to 20 amperes when the proper spring is installed for fuse size.
Molded Parts: Black Thermoplastic (UL 94V2).
Body halves have a .14" diameter hole for insulated wire.
Ambient Temperature: –40°C to +75°C.
Contact Rivet: Brass. Tin finish. Designed to accommodate #14 AWG stranded wire.
Assembled: Includes fuse listed and 19" loop of #14 AWG red vinyl insulated wire.
Unassembled: For assembly to #14 AWG wire.
OPTIONS:
150 215 is similar to **155** 120A except no fuse is supplied. It is intended for use with 3AG fuses rated up to 20 amperes.
UNIVERSAL IN-LINE FUSEHOLDER 155 100**:**
Supplied with 8" loop of #14 AWG red vinyl insulated wire and two springs in different lengths to accommodate SFE sized fuses.

*** Please refer to Fuseology section for information on proper fuseholder de-rating.**





ORDERING INFORMATION:

Unassembled		Assembled	
Catalog Number	For Fuse Size	Catalog Number	Fuse Installed
155 104U	1/4" x 5/8"	**155** 104A	SFE 4
155 106U	1/4" x 3/4"	**155** 106A	SFE 6
155 17.5U	1/4" x 7/8"	**155** 17.5A	SFE 7 1/2
155 109U	1/4" x 7/8"	**155** 109A	SFE 9
155 114U	1/4" x 1 1/16"	**155** 114A	SFE 14
155 120U	1/4" x 1 1/4"	**155** 120A	SFE 20

RoHS Heavy-Duty Bayonet Knob In-Line Type

SPECIFICATIONS:

Electrical: Intended for use at 32 volts or less with fuses rated up to 20 amperes when the proper spring is installed for full size.
Molded Parts: Body and knob are Black Thermoset (UL 94V0). Both body and knob have a .20" diameter hole for insulated wire.
Knob: Bayonet-lock type metal insert.
Ambient Temperature: –40°C to +125°C.
Contact Rivet: Brass. Tin plated. Designed to accommodate #14 AWG stranded wire.
Assembled: Includes fuse listed and 19" loop of #14 AWG red vinyl insulated wire.
Unassembled: For assembly to #14 AWG wire.
OPTIONS:
150 079 is similar to **155** 020A except no fuse is supplied. It is intended for use with 3AG fuses rated up to 20 amperes.
UNIVERSAL IN-LINE FUSEHOLDER 150 145**:**
Supplied with 15" loop of #14 AWG red vinyl insulated wire and three springs in different lengths to accommodate SFE sized fuses.
Fuseholders with other wire sizes or lengths available on special order.

*** Please refer to Fuseology section for information on proper fuseholder de-rating.**





ORDERING INFORMATION:

Unassembled		Assembled	
Catalog Number	For Fuse Size	Catalog Number	Fuse Installed
155 004U	1/4" x 5/8"	**155** 004A	SFE 4
155 006U	1/4" x 3/4"	**155** 006A	SFE 6
155 07.5U	1/4" x 7/8"	**155** 07.5A	SFE 7 1/2
155 009U	1/4" x 7/8"	**155** 009A	SFE 9
155 014U	1/4" x 1 1/16"	**155** 014A	SFE 14
155 020U	1/4" x 1 1/4"	**155** 020A	SFE 20

RoHS 2AG or 5 x 20mm Inline Fuseholders

SPECIFICATIONS:

Electrical: This fuseholder, part number 150274, is intended for use with 2AG and 5 x 20mm fuses. Maximum current ratings are 5 amperes at 32V for the 2AG size fuses and 10 amperes at 32V for the 5 x 20mm size fuses.
Body: Black Thermoplastic.
Terminals: Brass.
Wire: 16 Awg size; nominal o.d. 0.104"; color red.
Lead Pull Test: Will withstand 10 lb. pull.
Ambient Temperature: –40°C to +80°C.
ORDERING INFORMATION:
Catalog Number: 150 274

*** Please refer to Fuseology section for information on proper fuseholder de-rating.**



