

ASSEMBLY



SECTION A-A



SECTION B-B

Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

NOTE
Purchased assembly includes box, lid and 4 cover screws. Box and lid are made from Diecast Aluminum Alloy. Silicone Gasket Loctite #5950

PART NUMBERS	
1590X Enclosure	
Unfinished	1590X
Grey Textured Polyester Powder Paint - RAL 7038	1590XGY
Black Textured Polyester Powder Paint - RAL 9011	1590XBK
1590X Liquid Resistant Enclosure (Silicon Factory Installed Gasket)	
Unfinished	1590WX
Black Textured Powder Paint	1590WXBK
ACCESSORIES	
Recommended Torque: 75 ozf.in / 55 cN.m	
Black Textured Cover Screws (Pkg 100) [6-32 x 1/2" SS Type 304]	1590WMS100BK
Unfinished Cover Screws (Pkg 100) [6-32 x 1/2" SS Type 304]	1590WMS100
Standard Cover Screws	
Unfinished Cover Screws (Pkg 100) [6-32 x 1/2" Nickel Plated Screws]	1590MS100
Black Textured Cover Screws (Pkg 50) [6-32 x 1/2" Nickel Plated Screws]	1590MS50BK



BOX - INSIDE



LID - INSIDE

HAMMOND MANUFACTURING™

1590X

www.hammondmfg.com