482.6 mm (19″)/metric installation




Adaptor

for RNC
For installing 10″ components in 296.2 mm (1/2 19″) enclosures.

Material:
Sheet steel

Colour:
RAL 7035

U	Model No. DK
1	**7870.760**
4	**7870.765**



Spring nuts with screws

M5 x 10 mm/M6 x 10 mm for T-slot mounting angle
The spring nuts ensure flexible, secure mounting of accessory components on the T-slot of the FR(i) frame and on the T-slot mounting angles.

Supply includes:
50 spring nuts,
50 spring nuts, 10 mm, self-locking.

Design	Packs of	Model No. DK
Phillips-head, M6	50	**7000.990**
Multi-tooth 25, M5	50	**7856.755**



Assembly screws

M5 x 16 mm/M6 x 16 mm
For electronic equipment, 482.6 mm (19″) installed components and blanking plates.

Supply includes:
Plastic washers.

Design	Packs of	Model No. EL
Phillips-head screw M5	100	**2099.500**
Cheese-head screw M6	100	**2093.200**
Phillips-head screw M6	100	**2089.000**



Multi-tooth screw

M5 x 16 mm/M6 x 16 mm
For optimum transmission of torques, an extended tool life and increased safety and reliability when tightening and loosening screw connections.

Supply includes:
Plastic washers.

	Bit size	Packs of	Model No. DK
M5	Multi-tooth 25	100	**7094.500**
M6	Multi-tooth 30	100	**7094.600**