ratiopacPRO cases







ratiopacPRO with A - cover; B - front handle; C - 19" mounting bracket

Part no.: 24571-017

Features:

- The space-optimised version, interior and exterior dimensions correspond to a 19" subrack
- With front trim

Technical information:

Description	Height	Width W	Width W	Depth D
With front trim	3 U	42 HP	235.74 mm	315.5 mm

Dimensions table ratiopacPRO

Height			Width			
H	h	w	W	w1	w2	w
in U	in mm	in HP	in mm	in mm	in mm	in mm
3	132,55	112,35	28	164,42	177,62	198.12	142,82
42	235,54	248,74	269,24	213,94			
63	342,42	355,42	375,92	320,62			
84	448,90	462,10	482,60	427,30			

Components mountable in 15 mm depth grid

Depth			
D	d	D1	d2
Total depthin mm	Useable depthin mm	Plug-in depthin mm	Board depthin mm
255,5	235,5	175,5	160
235,5	220		
315,5	295,5	175,5	160
235,5	220		
295,5	280		
375,5	355,5	175,5	160
235,5	220		
295,5	280		
355,5	340		
435,5	415,5	175,5	160
235,5	220		
295,5	280		
355,5	340		
495,5	475,5	175,5	160
235,5	220		
295,5	280		
355,5	340		

Delivery comprises: in kit form

Item	Qty	Description
1	2	Side panel, Al, clear chromate
2	2	Side panel, Al, visible surface powder-coated, RAL 9006
3	2	Rear trim, diecast zinc, powder-coated, RAL 7016
3a	2	Front trim, diecast zinc, powder-coated, RAL 7016
4	4	Horizontal rail, Al, visible surface powder-coated, RAL 7016
11	2	Top cover and base plate, Al, internal surface conductive, visible surface powder-coated, RAL 9006, with GND/earthing connection, base plate with vent slots
12	4	Case foot, PC, black, with anti-slip protection
13	1	Assembly kit

Note:

- Dimensions marked with "-" are available on request, as well as other widths and depths