

BANANA PLUGS - JACKS


25-2531-1-02 / 25-2532-1-02 BANANA PLUG
15 AMPERES CAPACITY

25-2531-1-02 / 25-2532-1-02
FINISH

Standard size spring for standard size banana jacks. Supplied with solder lug and screw for panel mounting.







Part No.	Screw
25-2531-1	6-32 x.250
25-2532-1	8-32 x .250


COMPONENT	MATERIAL	(02) FINISH
Plug Body	Brass	Nickel
Spring	Beryllium Copper	Nickel
Lug	Brass	Tin


25-2259-X-03 BANANA PLUG

25-2259-X-03
FINISH

RATED FOR 5 AMPERES
CONTINUOUS DUTY

Miniature size spring to mate with miniature size (.104 dia.) banana jack. Spring, one piece heat treated beryllium copper. Plug body is heat treated to faciliate swaging.





Part No.	L	Panel
25-2259-2	.094	1/16
25-2259-3	.125	3/32
25-2259-4	.156	1/8

COMPONENT	MATERIAL	(03) FINISH
Plug Body	Brass	Gold
Spring	Beryllium Copper	Gold


01-2260-X-02 BANANA PLUG

01-2260-X-02
FINISH

RATED FOR 15 AMPERES
CONTINUOUS DUTY

Short size spring for standard size banana jacks. Plug body is heat treated to facilitate swaging.





Part No.	L	Panel
01-2260-2	.105	1/16
01-2260-3	.135	3/32
01-2260-4	.156	1/8

COMPONENT	MATERIAL	(02) FINISH
Plug Body	Brass	Nickel
Spring	Beryllium Copper	Nickel


25-2262-X-02 BANANA PLUG

25-2262-X-02
FINISH

RATED FOR 15 AMPERES
CONTINUOUS DUTY

Standard size spring for standard size banana jacks. Spring, one piece heat treated beryllium copper. Plug body is heat treated to facillitate swaging.





Part No.	L	Panel
25-2262-2	.094	1/16
25-2262-3	.125	3/32
25-2262-4	.156	1/8


COMPONENT	MATERIAL	(02) FINISH
Plug Body	Brass	Nickel
Spring	Beryllium Copper	Nickel


01-2251-X-044 BANANA PLUG

01-2251-X-044
FINISH

RATED FOR 5 AMPERES
CONTINUOUS DUTY

Miniature size spring to mate with miniature size (.104 dia.) banana jack. Plug body is heat treated to facilitate swaging.





Part No.	L	Panel
01-2251-2A	.093	1/16
01-2251-2	.105	1/16
01-2251-3	.135	3/32
01-2251-4	.156	1/8

COMPONENT	MATERIAL	(044)FINISH
Plug Body	Brass	Bright-Tin
Spring	Beryllium Copper	Bright-Tin


01-2258-X-044 BANANA PLUG

01-2258-X-044
FINISH

RATED FOR 5 AMPERES
CONTINUOUS DUTY

Miniature size spring to mate with miniature size (.104 dia.) banana jacks. Plug body is heat treated to facilitate swaging.






Part No.	L	Panel
01-2258-2	.094	1/16
01-2258-3	.125	3/32
01-2258-4	.156	1/8

COMPONENT	MATERIAL	(044)FINISH
Plug Body	Brass	Bright-Tin
Spring	Beryllium Copper	Bright-Tin

09-9141-1-044XX BANANA PANEL JACK INSULATED

09-9141-1-044XX
FINISH COLOR

RATED FOR 10 AMPERES
CURRENT




Part is completely insulated from chassis. Accommodates panels from 1/16" to 1/4" thick. Design of part accepts miniature banana plug. One piece turret contact allows sealed panel entry hole.

09-9140-1-044XX BANANA PANEL JACK INSULATED

09-9140-1-044XX
FINISH COLOR

RATED FOR 10 AMPERES CURRENT



Part is completely insulated from chassis. Accommodates panels from 1/16" to 1/4" thick. Design of part accepts miniature banana plugs. One piece turret contact allows sealed panel entry hole.

FOR ADDITIONAL SIZES AND MATERIALS, CONTACT FACTORY

BLK	BRN	RED	ORN	YEL	GRN	BLU	PUR	GRY	WHT
10	11	12	13	14	15	16	17	18	19

800-847-4162 (Outside N.Y.S.)
Ph: 212-777-6571 Fax: 212-991-0161
sales@concord-electronics.com
engineering@concord-electronics.com