Extract from the online catalog

FL MGUARD RS VPN ISDN

Order No.: 2989815

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2989815

Router with intelligent Firewall, data throughput up to 99 Mbps (Wire Speed), Stateful Inspection Firewall for optimum safety and extremely simple configuration, VPN as per IPsec, hardware encryption with up to 70 Mbps, integrated ISDN modem ISDN terminal adapter

Product notes

WEEE/RoHS-compliant since: 07/01/2007

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Commercial data

GTIN (EAN)	4 046356 299077
Note	Made-to-order
sales group	K006
Pack	1 pcs.
Customs tariff	85176200
Catalog page information	Page 113 (AX-2011)

Technical data

Interfaces

Interface 1	Ethernet
No. of ports	2
Connection method	RJ45

Transmission physics	Ethernet in RJ45 twisted pair
Transmission speed	10/100 MBit/s
Transmission length	100 m (per segment)
Signal LEDs	Supply voltage, data transmission, error, link, activity
Interface 2	Potential-free signaling contact
Connection method	Plug-in/screw connection via COMBICON
Interface 3	VPN - release button
Connection method	Connectable and optional LED

Function

Basic functions	Router with intelligent Firewall, VPN and an integrated ISDN terminal adapter
Management	Web based management, SNMP or over V.24 (RS-232)
Supported browsers	HTTPS support required
Processor	533 MHz
Status and diagnostic indicators	LEDs:P1, P2, Fault, State, Error, LAN, WAN

Network expansion parameters

Maximum conductor length ((twisted pair)	100 m

Supply voltage

Supply voltage	24 V DC
Residual ripple	3.6 V_{PP} (within the permitted voltage range)
Supply voltage range	9 V DC ... 36 V DC
Typical current consumption	170 mA

General data

Width	45 mm
Height	99 mm
Depth	112 mm
Mounting type	DIN rail
Type AX	Stand-alone
Weight	250 g
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C
Permissible humidity (operation)	10 % ... 95 % (no condensation)
Housing material	PA 6.6
Noise emission	EN 61000-6-4

Noise immunity	EN 61000-6-2:2005

Conformity with EMC directives

Developed in acc. with standard	IEC 61000-6.2
Test standard	IEC 61000-4-2 (ESD)
Test result	6 kV contact discharge, 8 kV air discharge
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	10 V/m (80-2000 MHz)
Test standard	IEC 61000-4-4 (burst)
Test result	2 kV power line, 1kV data line
Test standard	IEC 61000-4-5 (surge)
Test result	power line: 2 kV (line/earth), 1 kV (line/line), 1kV data line
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	3 V(10 kHz-150 kHz), 10 V (150 kHz-80 MHz)

Security functions

Dynamic Host Configuration Protocol (DHCP) support	Server or Relay Agent
Network Time Protocol (NTP) client	Client
Link Layer Discovery Protocol (LLDP)	As per protocol 802.2
Remote Syslog Logging	On externals server
Virtual private network (VPN) throughput	Up to 70 Mbps
Number of VPN tunnels	10 (Up to 250 with license possible)
Encryption methods	DES, 3DES, AES-128, -192, -256
Internet Protocol Security (IPsec) mode	ESP-Tunnel / ESP-Transport
Authentication	X.509v3 certificates with RSA or PSK
Data integrity	MD5, SHA-1
1:1 Network Address Translation (NAT) in the VPN	Supported
Firewall data throughput	Up to 99 Mbps
Firewall rules	Configurable stateful inspection firewall
Filtering	MAC and IP addresses, ports, protocols
Protection against	IP spoofing, DoS and Syn Flood Protection
Routing	Standard routing, NAT, 1:1-NAT, port forwarding

Certificates / Approvals

Certification	CUL Listed, UL Listed

Accessories

Item	Designation	Description
Cable/conductor		
2832250	FL CAT5 PATCH 0,3	Patch cable, CAT5, assembled, 0.3 m
2832263	FL CAT5 PATCH 0,5	Patch cable, CAT5, assembled, 0.5 m
2832276	FL CAT5 PATCH 1,0	Patch cable, CAT5, assembled, 1.0 m
2832221	FL CAT5 PATCH 1,5	Patch cable, CAT5, assembled, 1.5 m
2832629	FL CAT5 PATCH 10,0	Patch cable, CAT5, assembled, 10.0 m
2832289	FL CAT5 PATCH 2,0	Patch cable, CAT5, assembled, 2.0 m
2832292	FL CAT5 PATCH 3,0	Patch cable, CAT5, assembled, 3.0 m
2832580	FL CAT5 PATCH 5,0	Patch cable, CAT5, assembled, 5.0 m
2832616	FL CAT5 PATCH 7,5	Patch cable, CAT5, assembled, 7.5 m
2891369	FL CAT6 PATCH 12,5	Patch cable, CAT6, pre-assembled, 12.5 m
2891372	FL CAT6 PATCH 15,0	Patch cable, CAT6, pre-assembled, 15.0 m
2891576	FL CAT6 PATCH 20,0	Patch cable, CAT6, pre-assembled, 20.0 m
General		
2744788	FL MC 10BASE-T/FO G850	Fiber optic converter, for converting 10Base-T to multimode glass fiber, (850 nm), B-FOC (ST®) FO connection, supply 24 V DC
2891165	FL PF 2TX CAT5E	Patch field with two RJ45 CAT5e network connections
2891178	FL PF 8TX CAT5E	Patch field with eight RJ45 CAT5e network connections
2832991	FL RJ45 PROTECT CAP	Dust protection caps for RJ45 female connector
Plug/Adapter		
2744571	FL PLUG RJ45 GN/2	RJ45 connector, shielded, with bend protection sleeve, 2 pieces, green for crossed cables, for assembly on site. For connections that are crossed, it is recommended that the connector set with green bend protection sleeves is used.

2744856	FL PLUG RJ45 GR/2	RJ45 connector, shielded, with bend protection sleeve, 2 pieces, gray for straight cables, for assembly on site. For connections that are not crossed, it is recommended that you use the connector set with gray bend protection sleeve.

Tools

2744869	FL CRIMPTOOL	Crimping pliers, for assembling the RJ45 connectors FL PLUG RJ45..., for assembly on site

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057,USA
Phone (800) 888-7388
Fax (717) 944-1625
http://www.phoenixcon.com

© 2012 Phoenix Contact
Technical modifications reserved;