

632 Arch Street, POB 726 Meadville, PA 16335 USA 814-724-6440
Contact Webmaster
© June 6, 2005

Nylon Round Spacer

- Molded Nylon
- An excellend insulator, the nylon spacer's surface lubricity allows wires to be routed against spacer without fear of chafing the insulation
- Natural milky white finish
- Relatively low operating temperature
- Nylon spacers and standoffs can be manufactured in alternative dimensions per special order







LENGTH		O.D.	HOLE CLEARANCE SIZE				
			#2	#4	#6	#8	#10
.125	1/8	3/16	9160	9180			
		1/4		4000	4001	4002	
		5/16			4065A	4067A	4069A
		3/8				4068A	4070A
.187	3/16	3/16	9161	9181			
		1/4		4003	4004	4005	
		5/16			4065B	4067B	4069B
		3/8				4068B	4070B
.250	1/4	3/16	9162	9182			
		1/4		4006	4007	4008	
		5/16			4065C	4067C	4069C
		3/8				4068C	4070C
.312	5/16	3/16	9163	9183			
		1/4		4009	4010	4011	
		5/16			4065D	4067D	4069D
		3/8				4068D	4070D
.375	3/8	3/16	9164	9184			
		1/4		4012	4013	4014	
		5/16			4065E	4067E	4069E
		3/8				4068E	4070E
.437	7/16	3/16	9165	9185			
		1/4		4015	4016	4017	
		5/16			4065F	4067F	4069F
		3/8				4068F	4070F
		3/16	9166	9186			

		3/8				4068F	4070F
.500	1/2	3/16	9166	9186			
		1/4		4018	4019	4020	
		5/16			4065G	4067G	4069G
		3/8				4068G	4070G
.562	9/16	3/16	9167	9187			
		1/4		4021	4022	4023	
		5/16			4065H	4067H	4069H
		3/8				4068H	4070H
.625	5/8	3/16	9168	9188			
		1/4		4024	4025	4026	
		5/16			4065J	4067J	4069J
		3/8				4068J	4070J
.687	11/16	3/16	9169	9189			
		1/4		4027	4028	4029	
		5/16			4065K	4067K	4069K
		3/8				4068K	4070K
.750	3/4	3/16	9170	9190			
		1/4		4030	4031	4032	
		5/16			4065L	4067L	4069L
		3/8				4068L	4070L
.812	13/16	3/16	9171	9191			
		1/4		4033	4034	4035	
		5/16			4065M	4067M	4069M
		3/8				4068M	4070M
.875	7/8	3/16	9172	9192			
		1/4		4036	4037	4038	
		5/16			4065N	4067N	4069N
		3/8				4068N	4070N
.937	15/16	3/16	9173	9193			
		1/4		4039	4040	4041	
		5/16			4065P	4067P	4069P
		3/8				4068P	4070P
1.000	1	3/16	9174	9194			
		1/4		4042	4043	4044	
		5/16			4065Q	4067Q	4069Q
		3/8				4068Q	4070Q