Pomona®

Model 4279 & 4279N
Bantam Plug Cable Assembly





SCHEMATIC

FEATURES:

- Bantam plugs are molded directly to the cable for optimum durability

MATERIALS:

Bantam Plug: Body – Brass, Insulation – PVC, Color: Black
Audio Cable: Two Conductor Twisted Pair With Spiral Shield, Color: Gray
Capacitance: 40 pF/Ft.
Conductors: 22 AWG, Stranding: 7 x 30
Jacket: PVC, O.D. .180" (4,6mm) Nom., Marking: "POMONA 4279-XX"
Finish: 4279N Brass nickel plated

RATINGS:

Operating Temperature: +50°C (+122°F)
Operating Voltage: 300 VRMS

ORDERING INFORMATION: XX = Cable Length, Standard Lengths:
Model 4279-XX :12" (30,5 cm), 24" (61 cm), 36" (91,44cm), 48" (121,92cm), 60" (152,4cm)
4279N-XX: 24" (61 cm), 36" (91,44cm), 60" (152,4cm)
Additional lengths can be quoted upon requested.
Ordering Example: 4279-12, Cable length is 12" with non-plated Bantam connector
4279N-24, Cable length is 24 with brass nickel plated Bantam connector

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (,51 mm), .xxx = ± .005" (,127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA