AK12 – Polystyrene and Polycarbonate - 250 x 200 mm (9.84 x 7.87 in.)

Standard Features

- **Protection Level:** IP65
- **Technical:** Fits 12 Circuit Breaker Poles
  Knockout Sidewalls and Installed Double Membrane Seals
  Tinted Transparent Door
- **UL Recognized Enclosure Materials:** Polystyrene or Polycarbonate
- **Door Material:** Polycarbonate
- **Gasket Material:** Polyurethane
- **Material Temperature Range:** Polystyrene
  -25˚C to 70˚C (-13˚F to 158˚F)
  Polycarbonate
  -40˚C to 120˚C (-40˚F to 248˚F)
- **Color:** Light Gray
- **Included Accessories:** DIN Rail, 2x12 Pole Ground/Neutral Terminal Strip, Filler Strips, (8) M20 Double Membrane Seals




AK12


Ordering Information	Cat. No.	Type	Dimensions mm (in) Length	Width	Height	Std. Pk.
Polystyrene						
Enclosure	735-412	AK12	250 mm (9.84 in)	200 mm (7.87 in)	122 mm (4.80 in)	1
Polycarbonate						
Enclosure	736-412	AKi12	250 mm (9.84 in)	200 mm (7.87 in)	122 mm (4.80 in)	1


Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
Key Lock	706-102	KL2	1
Terminal	790-211	PE/N Terminal - 12 pole	1
Filler Strip	799-012	108 mm piece (6 divisions)	1

Please refer to pages 136-140 for additional accessories and detailed information.







Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Altech:
736-412