Cable Gland *Standard Straight-Through - Stainless Steel*

Material:
- Body: Stainless Steel 1.4404 / INOX 316L
- Seal: Neoprene
- Clamping insert: Polyamide 6
- Sealing ring for outer thread: Nitril

Technical properties:
- Seal rings included
- Maximum strain relief through clamp range
- Gas tight- and watertight



Metric Thread


M 12 x 1.5	1.5-5	**4220860**	100
M 12 x 1.5	4.5-6.5	**4220850**	100
M 16 x 1.5	2.5-7	**4220861**	50
M 16 x 1.5	5-9.5	**4220851**	50
M 20 x 1.5	4-10	**4220862**	50
M 20 x 1.5	8-13	**4220852**	50
M 25 x 1.5	5-13	**4220863**	25
M 25 x 1.5	9-16	**4220853**	25
M 32 x 1.5	7-17	**4220864**	20
M 32 x 1.5	12-21	**4220854**	20
M 40 x 1.5	10-22	**4220865**	10
M 40 x 1.5	16-27	**4220855**	10
M 50 x 1.5	17-29	**4220866**	5
M 50 x 1.5	23-35	**4220856**	5
M 63 x 1.5	28-40	**4220867**	5
M 63 x 1.5	36-48	**4220857**	5

PROTECTION IP68 RATING

Temperature Range
-25 to 100°C (-13 to 212°F)

Dimensions

Thread Size	H mm	E mm	L mm	ØC mm	ØP mm	ØThread mm
M12x1.5	14	5	25	6.6	6.6	12
M16x1.5	17	5	28	9.7	10	16
M20x1.5	22	6	32	13.2	13.5	20
M25x1.5	27	7	35	16.2	16.5	25
M32x1.5	34	8	38	21.5	22	32
M40x1.5	42	8	41	27.5	28	40
M50x1.5	55	9	46	35.5	36	50
M63x1.5	65	10	54	48.5	50	63



Locknuts sold separately, see page 24.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Altech:

7217701 7217702