Temperature Probes

Use with thermocouple thermometers and multimeters with Type K and Type J functions

TP870

872502

TP873

TP875

Bead Wire Type K and J Temperature Probes

- **TP870** Bead wire; 39" (1m) cable; subminiature Type K connector; (-40 to 482°F/-40 to 250°C)
- **872502**....Bead Wire; 39" (1m) cable; subminiature Type J connector; Range (-40 to 392°F/-40 to 200°C)
- **TP873**.....Bead wire; 36" (.91m) cable; subminiature Type K with banana connector; Range (-40 to 572°F/-40 to 300°C)
- **TP875**.....High temperature bead wire probe; 39" (1m) cable; subminiature Type K with banana connector; Range (-40 to 1000°F/-40 to 538°C)

TP882

Type K and J Temperature Probes

Penetration

- **TP882**..... 8" (203mm)High Temperature Penetration Probe; Stainless steel 304; 72" (183cm) cable; probe diameter 0.13" (3.3mm); Type K, Range (-40 to 1000°F/-40 to 538°C)

General Purpose

- **871515**.... 4" (100mm) General Purpose Probe; 39" (1m) cable; probe diameter 0.126" (3.2mm);Type K, Range (-40 to 1292°F/-40 to 700°C)
- **881605**.... 5.9" (152mm) General Purpose Probe; Stainless steel 316; 70.8" (1.8m) coiled cable; probe diameter 0.126" (3.2mm);Type K, Range (-40 to 1292°F/-40 to 700°C)
- **801515**.... 4" (150mm) General Purpose Probe; 39"(1m) cable; diameter 0.126" (3.2mm); Type J, Range (-40 to 842°F/-40 to 450°C)

Immersion

- **881603**.... 6" (150mm) Immersion Probe; Stainless steel 316; 70.8" (1.8m) coiled cable; diameter 0.126" (3.2mm); Type K, Range (-40 to1292°F/-40 to 700°C)

Surface

- **881602**.... 6" (150mm) Surface Probe; Stainless steel 304; 70.8" (1.8m) coiled cable; diameter 0.314" (8mm); Type K, Range(-40 to 1472°F/-40 to 800°C)
- **861616**.... Magnetized Type K Surface Probe; 6' teflon cable, 1" x 0.75" surface area; Range -40°F to 482°F (-40°C to 250°C); Includes replacement temperature element



871515, 881605, and 801515 general purpose probes

881602 surface probe

881603 immersion probe



881616 surface probe

Specifications subject to change without notice.
Copyright © 2007-2011 Extech Instruments Corporation. All rights reserved including the right of reproduction in whole or in part in any form.