Basic Rack PDU

Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13

AP9565

Email Technical Specifications
Printer Friendly



APC Basic Rack PDU , Input: 230V , Input Connections: IEC-320 C20 , Cord Length: 8.2 feet (2.5 meters) , Output: 208V, 230V , Output Connections: IEC 320 C13

Includes: Installation guide, Rack Mounting brackets

Standard Lead Time : Usually in Stock

More Images

Technical Specifications | Product Overview | Documentation | Options | Compare Models

Output

Nominal Output Voltage	208V,230V
Maximum Total Current Draw per Phase	16A
Output Connections	(12) IEC 320 C13

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C20
Cord Length	2.5 meters
Number of Power Cords	1
Maximum Input Current per phase	16A
Load Capacity	3680 VA

Physical

Net Weight	2.05 KG
Maximum Height	44.00 mm
Maximum Width	447.00 mm
Maximum Depth	57.00 mm
Shipping Weight	3.64 KG
Shipping Height	70.00 mm
Shipping Width	464.00 mm
Shipping Depth	229.00 mm
Color	Black

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	cUL Listed,CE,CSA,GOST,Queensland Australia,UL 60950,UL Listed,VDE
Standard Warranty	2 years repair or replace
ROHS/WEEE Compliance	RoHS 7b Exemption

Copyright © American Power Conversion Corp., all rights reserved