# Panel-Mount—Indicating Fuseholder
## For ¼″ × 1¼″ Fuses

# HK
# Series

Catalog Symbol: HKL, HKR, HKT, HKU, and HKX

**Panel-Mount—Indicating**

**Ampere Rating:** 15 and 20A

**Temperature Rating (RTI):** 130°C

**Agency Information:**

*UL Recognized, Guide IZLT2, File E14853

*CSA Certified, Class 6225-01, File 47235

Electrical Ratings

| Catalog Symbol | Amps | Lamp | | Knob Color | Knob Type |
|---|---|---|---|---|---|
| | | Volts AC | Type | | |
| HKL * | 15 | 90-250 | Neon | Clear | Octagon |
| HKL-X * | 15 | 90-250 | Neon | Clear | Flat Sided |
| HKR | 20 | 22-30 | Incandescent | Amber | Octagon |
| HKT | 20 | 13-22 | Incandescent | Amber | Octagon |
| HKU | 20 | 4-6 | Incandescent | Red | Octagon |
| HKX | 20 | 22-33 | Incandescent | Amber | Flat Sided |

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 314-527-1270 for more information.

Dimensional Data




**Punched Mounting Hole**




General Information:

- For panels up to 3⁄16″ (4.8mm) thick.
- Vibration resistant.
- For ¼″ × 1¼″ fuses.
- Light comes on when fuse opens.
- Steel nut – 9351.
- Neoprene washer – 6276.
- Line connection is the back terminal.
- Do not put tension on line (rear) terminal.

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.