Search Product:

Submit

[Advanced]

- Adapters & power supplies
- Batteries & chargers
- Cables & accessories
- Connectors
- Consumer products & pc acc.
- Electronic components
- High-q tools & dmm's
- Led products & lamps
- Light products
- Loudspeakers & pa systems
- Perel tools
- Security products
- Velleman kits & oscilloscopes

ROHS Info

HIGH - Q TOOLS & DMM'S > MULTIMETERS > DIGITAL MULTIMETERS >

3 ½ DMM - 30 RANGES / 10A / TEMPERATURE IN FAHRENHEIT / CAPACITANCE / FREQUENCY

Order Code: DVM890F

Features

- very complete model
- low-battery indication, overload protection and automatic deactivation
- transistor, diode and audible continuity test
- DC current max. 20A, DC voltage max. 1000V
- AC current max. 20A, AC voltage max. 700V
- resistance measurements: up to 20Mohm
- capacitance measurements: from 2000pF to 20µ F
- frequency measurements: max. range 20kHz
- temperature test range: from 32°F to 104°F through built -in sensor
- K-type thermocouple measuring range: from -58°F to 1832°F
- with holster
- packaging: blister

Specifications

- DC voltage: 200m/2/20/200/1000V
  - basic accuracy: ± 0.5%
  - input impedance: 10Mohm
  - maximum input: 1000V
- AC voltage: 2/20/200/700V
  - basic accuracy: ± 0.8%
  - input impedance: 10Mohm
  - frequency range: 40 - 400Hz
  - maximum input: 750V
- DC current: 2m/20m/200m/20A
  - basic accuracy: ± 0.8% (± 2.0% for 20A range)
  - overload protection: 0.2A (20A for 20A range)
- AC current: 20m/200m/20A
  - basic accuracy: ± 0.8% (± 3.0% for 20A range)
  - overload protection: 0.2A (20A range not fused)
- resistance: 200/2k/20k/200k/2M/20M/200M
  - basic accuracy: ± 0.8% (± 5.0% for 200M range)
  - overload protection: 250V
- capacitance: 2000p/20n/200n/2µ /20µ F
  - accuracy: ± 2.5%
- inductance: -
  - accuracy: -
- frequency: 20kHz
  - basic accuracy: ± 1.0%
  - overload protection: 250V DC/AC
- temperature: -58°F to 1832°F
  - basic accuracy: ± 0.75%
- overrange: yes "1"
- continuity buzzer: yes
- transistor test: yes
- diode test: yes
- low-battery indication: yes
- maximum display: 1999
- LCD display size: 1.2" x 2.4"
- ranging mode: manual
- data hold: no
- backlight: no
- dimensions: 3.5" x 6.7" x 1.5"
- weight (with battery): ± 12.0oz
- power supply: 9V battery
- packing: blister
- accessories: manual / test leads / holster / battery / temp. probe
- auto power-off: yes

Stock Info

- Inner carton: 5
- Outer Carton: 20
- EAN Barcode:
- Packaging:

(C) 2005 Velleman Components N.V.
[Disclaimer]