Fuse Blocks, Holders and Accessories

POWR-SAFE "Dead Front" Holders



Littelfuse POWR-SAFE "Dead Front" holders provide optimum protection to personnel. Indicating and non-indicating versions are available in 1, 2, 3, or 4 poles for Class CC and Midget fuses.

Features/benefits

- Meets "Dead Front" requirements
- Mountable on 35mm Din Rail
- Blown fuse identification (Indicating versions only)
- Easy installation and removal of fuses. No special fuse pullers or tools required.
- UL Listed for branch circuit protection (Class CC versions only)
- Compact design
- Ventilated design for cooler operation
- Indicates above 80 volts (ID versions only)

Ordering information


Indicating Part Number	Non-Indicating Part Number	Fuse Type	Number of Poles
LPSC001ID	LPSC001	Class CC	1
LPSC002ID	LPSC002	Class CC	2
LPSC003ID	LPSC003	Class CC	3
LPSC004ID	LPSC004	Class CC	4
LPSM001ID	LPSM001	Midget	1
LPSM002ID	LPSM002	Midget	2
LPSM003ID	LPSM003	Midget	3
LPSM004ID	LPSM004	Midget	4

Multi-pole Assembly Kit: Order No: CYHP001
(Kit contains 20 connector pincers and 10 handle pins.)

NOTE: Contact factory for DC rated versions.

Dimensions in inches (mm in parentheses)

- LPSM/LPSC POWR-SAFE Holders



Specifications

Voltage Rating: 600 Volts AC/DC
Ampere Rating: 30 amperes
Interrupting Rating: 200 kA (Class CC)
100 kA (Midget)
Terminal type: Pressure plate
Suggested Torque: 17.7 lb.
Wire Range: #6—#14CU

Material: Thermo-Plastic
Flammability Rating: 94VO
Approvals: UL Listed (LPSC File No: E14721)
UL Recognized (LPSM File No: E14721)
CSA Certified (LPSC/LPSM File No: LR7316)
CE Certified

© 2005 Littelfuse • POWR-GARD™ Products Catalog